

ESSENTIAL MED 85 DIN

according to DIN 13277

Equipment

- 3 drawers and 1 shelf
- Standalone or undercounter installation
- Automatic defrosting
- Condensate evaporation
- Digital temperature display
- Antifreeze
- Visual and audible alarm signal, even in the case of power failure
- Minimum/maximum temperature memory



Suitable for built-in and under-counter installation

Smallest built-in and under-counter medicine refrigerator in accordance with DIN 13277.



User-friendly

with automatic defrosting and electronic temperature control, which can be installed in the front of furniture.

- **External housing** made from galvanised sheet steel (rustproof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Interior made from** impact-resistant, white plastic with moulded-in shelves.
- **Interior** can be customised (surcharge may apply). See optional equipment.
- **Extra-thick insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Automatic defrosting** with time and temperature monitoring.
- **Forced-air cooling** with cross-flow blower, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Warning functions:** visual and audible alarm signal, even in the case of temperature deviations and power failure. In the case of power failure, the monitoring unit remains in operation for approx. 72 hours on battery power. Door open alarm after 60 seconds.
- **Alarms** can be forwarded via email or SMS using the Kirsch EVOLUTION CLOUD Module (optional).
- **Electronic temperature** control with membrane keyboard and digital temperature display in the interior.
- **Condensate evaporation** in the refrigerating machine interior.
- **Statically ventilated refrigerating machine**, hermetically sealed, energy saving, low noise, easy to service.
- **Antifreeze** against sub-zero temperatures.

Specification

Capacity	80 litres
Temperature setting	approx. +2 °C to +12 °C
Voltage	220 – 240 V, 50 and 60 Hz
Power consumption	102 watts
Normal consumption	0.71 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	148 watts
Overall dimensions (including distance from wall)	w x d x h = 47 x 51 x 74 cm
useable dimensions	w x d x h = 34 x 32 x 63 cm *
Exterior dimensions with door open at 90°	w x d = 47 x 96 cm
Shelf size	23 x 37.8 cm
Drawer inner dimensions	w x d x h = 34 x 32 x 5.6 cm
Max. load: drawer/shelf	9.5 kg/25 kg
Weight	Net weight 32 kg, gross weight 38 kg
Temperature deviation	+/-1.15 °C
Noise emission	38.5 dB(A)

*(Usable depth at the bottom is 15 cm less)

Optional equipment

KIRSCH refrigerators and freezers offer numerous equipment options that can be retrofitted.



Lockable drawer (top)

Protects special refrigerated goods from unauthorised access.



Condensation tray

for manual draining of condensation water.



Additional length and cross dividers

for the optimum organisation of your refrigerated goods.



Additional Shelves

Wire shelves, robust with load capacity up to 40 and 50 kg.



Access Port

Simple insertion of an external temperature sensor with integrated cable feed-through.



Equipped with castors

Equipped with steering and fixed castors.



Door coupling


Connects the furniture door to the device.



Decorative frame


Made of stainless steel, allows to cover door with a decorative panel (thickness max. 2 mm).

Equipment for temperature documentation



External PT100/PT1000 with cold block

Additional temperature sensor
for connection to existing/ex-
ternal monitoring system.



KIRSCH EVOLUTION CLOUD- Module

Maximum storage safety
through optimal connectivity
and real-time monitoring. *

* For more information about our cloud, please contact us.

Philipp Kirsch GmbH
Im Lossenfeld 14
77731 Willstätt

Telefon: +49 (0) 781 9227-0
Telefax: +49 (0) 781 9227-200
info@kirsch-medical.de

www.kirsch-medical.com



You can find our complete
product overview on our
website:
www.kirsch-medical.com