

Series BACMY11 Grey

Certified according to EN14470-1
standard Type 90 & EN16121

**FIRE-RESISTANT
CERTIFIED**
90 minutes (TYPE 90)



Alarm system AT100



Painted steel shelf
RIP60VMY11



Closing system



EOF232BACMY11



EOF239BACMY11

Closing system allowing keeping the doors open

→ TECHNICAL FEATURES:

- Completely made of an electrogalvanized steel plate with a thickness of 1 - 1,5 mm, cold bent - Grey RAL7035
- External finishing in acidproof epoxy resin and passage through a thermal tunnel at 200 °C
- Cabinet isolation through some high density rock wool panels and some calcium sulphate panels
- Internal finishing with melamine panels highly resistant to chemical and aggressive vapours
- Structure allowing replacing spare parts if necessary
- Automatic door closing when the ambient temperature exceeds 50 °C
- 30 mm thermo-expanding isolation seals which in case of temperature rise ensure a perfect cabinet sealing according to standard EN14470-1
- Air inlet and outlet with certified fire dampers closing ducts when the temperature exceeds 70 °C according to standard DIN 4102-6.
- Prearrangement for ventilation through a Ø 100 mm flange for an external connection or a filtering ventilation system (see the chapter on ventilation)
- Closing and locking system of the doors allowing keeping the doors opened and closing them automatically in case of ambient temperature higher than 50 °C
- Spark resistant hinge ensuring a perfect door solidity
- Cabinet equipped with earthing
- Leveling jacks
- Door key lock
- 3 shelves made of painted or stainless steel (optional) whose height can be adjusted, 1 retention tray with grid
- Shelf fastening on some aluminium eyelets excluding all risks of spark
- Fire tested shelves
- ISO 3864 : Pictogram signalling
- Certified as fire-resistant for **90 minutes**, according to standard **EN14470-1 BV (Bureau Veritas)**
- Certified according to standard **EN16121 BV (Bureau Veritas)**

→ SERIES BACMY11

CODE	DESCRIPTION	EXTERNAL DIMENSIONS (WxDxH) mm	INTERNAL DIMENSIONS (WxDxH) mm	INTERNAL EQUIPMENT	STORAGE CAPACITY*	Weight (Kg)
EOF239BACMY11**	Cabinet series BACMY11 with 1 door	595x600x1950	496x446x1540	3 shelves made of painted steel (max. load 60 Kg evenly distributed) + 1 retention tray with grid (capacity 20 Litres)	80/100	209
EOF232BACMY11	Cabinet series BACMY11 BASIC with 2 doors	1200x600x1950	1095x446x1540	3 shelves made of painted steel (max. load 80 Kg evenly distributed) + 1 retention tray with grating (capacity 45 Litres)	160 / 200	349

*Approximate capacity in bottles holding 1 litre per cabinet

**Left door opening. Add «D» to the item code for the right door opening

→ INTERNAL EQUIPMENT (optional)

CODE	DESCRIPTION	DIMENSIONS (WxDxH) mm	RETENTION VOLUME (LITRES)	STORAGE CAPACITY*
RIP60VMY11	Additional shelf made of painted steel for cabinet with 1 door W600	493x420x39	7	20 / 25
RIP120VMY11	Additional shelf made of painted steel for cabinet with 2 doors	1094x420x39	16	44 / 55
RIP60MY11	Additional shelf made of stainless steel for cabinet with 1 door W600	493x420x39	7	20 / 25
RIP120MY11	Additional shelf made of stainless steel for cabinet with 2 doors	1094x420x39	16	44 / 55
RIPGI	Additional rotating shelf for cabinet with 1 door			
PS50SMY11	Replacement system with closing thermal fuse - left door	-	-	-
PS50MY11	Replacement system with closing thermal fuse - right door	-	-	-
ZOCPAL60MY11	Pallet truck base plate W600	595x600x110	-	-
ZOCPAL120MY11	Pallet truck base plate W1200	1200x600x110	-	-
CHEMIROLL	Wheel board to move the cabinets (the code ZOCPALMY11 is necessary)	-	-	-
CSFR127	Internal cooling system of the storage cabinet for products with a low flammability degree for high cabinet with 1 door W600	-	-	-
CSFR128	Internal cooling system of the storage cabinet for products with a low flammability degree for high cabinet with 2 doors	-	-	-

*Approximate capacity in bottles holding 1 litre

→ VENTILATION (optional)*

CODE	DESCRIPTION	DIMENSIONS (WxDxH) mm
DIAM125BP	Fresh air box holding box for high cabinet with 1 or 2 doors - outlet Ø: 125 mm (filter excluded)	290x290x270
CSF100BPAMY11	Fresh air box ATEX with power cable - outlet diam. 125 mm	350x370x500
K89006	Activated charcoal filter for organic solvents - series EFOMY11 (to replace at least 3 times a year)	235x110x15
GFKIT100	External connection kit (1 metre of hose diam. 100 mm and 2 clamps)	Ø 100 - W 1000 mm
CFN	Fresh air box with molecular filtration according to NFX15-211 standard, with visual and audible alarm	550x500x220
CFNL	Molecular filtration box manufactured, without alarm	550x500x220
CFNCO	Hour counter for CFN	
EOAS	Activated charcoal filter for solvents (prefilter included)	510x405x60
EOBE	Activated charcoal filter for acids (prefilter included)	510x405x60
EOMP	Activated charcoal filter for solvents and acids (prefilter included)	510x405x60
EOPF	Prefilter	510x405x15
EOPFO	ACTIVATED carbon filter for FORMALINE (for CFN)	

*To obtain the complete list of the connection accessories, see the chapter on ventilation of this catalogue and the current price list