

## Series ECO MULTIRISK Glazed doors



EOB120G



EOB124G



External hinge made of plastic  
resistant to corrosion

Modular solutions  
to store  
your chemicals



EOB60G



EOB62G



EOB63G

### → TECHNICAL FEATURES:

- Completely made of an electrogalvanized steel plate with a thickness of 15/10 mm, cold bent
- External finishing made of acidproof epoxy resin 90 microns Grey RAL7035 and passage through a thermal tunnel at 200 °C
- Construction in one piece with leveling jacks
- Division in 2, 3 or 4 compartments for storing separately the different families of nonflammable chemical products
- Swing doors with single wall and polycarbonate glass, highly resistant to chemical attacks
- Key lock
- Door opening with an angle of 110°
- External hinge made of plastic resistant to corrosion
- Compartments equipped with **fixed** retention shelves made of **plasticated, painted** and **stainless** steel whose height can be adjusted
- Ø 125 mm connection collar
- Standardized pictograms according to standards ISO 3864

## → SERIES ECO MULTIRISK GLAZED DOORS

CODE	DESCRIPTION	EXTERNAL DIMENSIONS (WxDxH) mm	INTERNAL DIMENSIONS (WxDxH) mm	INTERNAL EQUIPMENT	STORAGE CAPACITY*	Weight (Kg)
EOB60G	Cabinet with 1 glazed door 1 compartment	600x600x1950	595x540x1864	3 shelves made of <b>plasticated</b> steel (max load 40 Kg evenly distributed)	105	68
EOB62G	Cabinet 2 glazed doors 2 superimposed compartments	600x600x1950	595x540x930+930	Compartment for ACIDS: 2 shelves made of <b>plasticated</b> steel Compartment for BASES: 2 fixed shelves made of <b>stainless</b> steel (max load 40 Kg evenly distributed)	140	70
EOB63G	Cabinet 3 glazed doors 3 superimposed compartments	600x600x1950	595x540x618+618+618	Compartment for ACIDS: 2 shelves made of <b>plasticated</b> steel Compartment for BASES: 2 shelves made of <b>stainless</b> steel Compartment TOXICS: 2 shelves made of <b>painted</b> steel (max load 40 Kg evenly distributed)	210	73
EOB120G	Cabinet with 2 glazed doors 1 compartment	1200x600x1950	1130x540x1864	3 shelves made of <b>painted</b> steel (max load 80 Kg evenly distributed)	210	125
EOB124G	Cabinet with 4 glazed doors 4 compartments (2+2)	1200x600x1950	568+568x540x930+930	Compartment for ACIDS: 2 shelves made of <b>plasticated</b> steel Compartment for BASES: 2 shelves made of <b>stainless</b> steel Compartment TOXICS: 2 shelves made of <b>painted</b> steel Compartment for HARMFUL PRODUCTS: 2 shelves made of <b>painted</b> steel (max load 40 Kg evenly distributed)	280	135

\*Approximate capacity in bottles holding 1 litre per cabinet

## → INTERNAL EQUIPMENT (optional)

CODE	DESCRIPTION	DIMENSIONS (WxDxH) mm	RETENTION VOLUME (LITRES)	STORAGE CAPACITY*
EOB60R	Additional fixed shelf made of <b>plasticated</b> steel for cabinet with 1 door	595x539x39	12	35
EOB60RI	Additional fixed shelf made of <b>stainless</b> steel for cabinet with 1 door	595x539x39	12	35
EOB120R	Additional fixed shelf made of <b>plasticated</b> steel for cabinet with 2 doors	1130x539x39	22	70
EOB120RI	Additional fixed shelf made of <b>stainless</b> steel for cabinet with 2 doors	1130x539x39	22	70
EOB124R	Additional <b>plasticated</b> shelf for cabinet with 4 doors	576x537x39	12	38
EOB124RI	Additional <b>stainless</b> steel shelf for cabinet with 4 doors	576x537x39	12	38
TIM24	Daily counter	-	-	-
ALLARME	Alarm system for «open doors»	-	-	-

\*Approximate capacity in bottles holding 1 litre

## → VENTILATION (optional)

CODE	DESCRIPTION	DIMENSIONS (WxDxH) mm
DIAM125BP	Fresh air box with filter holding box for high cabinet with 1 or 2 doors - outlet Ø 125 mm (filter excluded)	290x290x270
RSOLCA	Activated charcoal filter for motor DIAM125BP - (to replace at least twice a year)	235x110x15
F125	Ø 125 mm connection collar for underbench cabinets	Ø125 mm
RE1000	Fan flow controller (to be ordered with the fan DIAM125BP)	-
GFKIT125	Connection kit: 1 metre of flexible sheath Ø 125 mm and 2 clamps	Ø 125 mm
CFN	Fresh air box with molecular filtration according to standard NFX15-211, with visual and audible alarm	550x500x220
CFNL	Molecular filtration box manufactured, without alarm	550x500x220
CFNCO	Hour counter for CFN	
CFNUB	Filtration box certified according to standard NFX15-211 for underbench cabinets, equipped with wheels, 2 ventilation outlets, with visual and audible alarm	400x500x650
CFNUBL	Filtration box certified for underbench cabinets, equipped with wheels, 2 ventilation outlets	400x500x650
EOAS	Activated charcoal filter (prefilter included)	510x405x60
EOBE	Activated charcoal filter for acids (prefilter included)	510x405x60
EOMP	Activated charcoal filter for solvents and acids (prefilter included)	510x405x60
EOPF	Prefilter	510x405x15

\*To obtain the complete list of the connection accessories, see the chapter on ventilation of this catalogue and the current price list