


Dial Indicators

workshop grade

- standard quality
- e.g. for workshop use

- solid brass housing, matt chrome finish, adjustable tolerance fingers
- spindle and stem stainless steel and hardened
- with turnable scale by outer ring, for easy zero setting








ART N° 241131



ART N° 241101




ART N°	 mm	 mm			 mm	A mm	B mm	C mm	D-ø mm	CC 
			yes	no						
241101	0 – 10	0.01	—	X	1	43.0	22.0	8.2	57	on request
241103	0 – 1	0.001	—	X	0.2	33.5	22.0	8.0	57	on request
241131	0 – 10	0.01	✓	—	1	43.0	22.0	8.2	57	on request

Dial Indicators

DIN 878

- top quality, for the workshop and inspection room

- metal housing, matt chrome finish
- spindle and stem stainless steel and hardened
- adjustable tolerance fingers
- with flat backcover and backcover with lug
- with turnable scale by outer ring, for easy zero setting








ART N° 241118



ART N° 241119

DIN


ART N°	 mm	 mm			 mm	A mm	B mm	C mm	D-ø mm	CC 
			yes	no						
241118	0 – 10	0.01	—	X	1	40	19.5	8	60	on request
241119	0 – 10	0.01	✓	—	1	40	19.5	8	60	on request

Käfer • Dial Indicators






DIN 878

- sturdy design, for workshop use and calibration purposes

- solid brass housing, matt chrome finish
- stem and spindle stainless steel, hardened and lapped
- adjustable tolerance fingers, from 0.001 mm with factory accuracy
- with turnable scale by outer ring, for easy zero setting



DIN

ART N°	 mm	 mm			 mm	A mm	B mm	C mm	D-ø mm	CC 
			yes	no						
240101	0 – 10	0.01	—	X	1.0	40	18.5	7.5	58	on request
240103	0 – 1	0.001	—	X	0.2	40	18.5	7.5	58	on request
240106	0 – 5	0.001	—	X	0.2	40	18.5	7.5	58	on request
240131	0 – 10	0.01	✓	—	1.0	40	18.5	7.5	58	on request
240133	0 – 1	0.001	✓	—	0.2	40	18.5	7.5	58	on request