



Melting Point Apparatus LDMP-B11

www.labtron.com | info@Labtron.com

Overview

Melting Point Apparatus LDMP-B11 offers desktop design, Semi-automatic detection method, with cooling function. Equipped with Peltier precise temperature function, In line with international standards such as CE & ISO for determination of the melting point of oils and fats. With addition of either high-definition camera or high definition video and camera technology, to delivers accurate, stable results, and user can clearly see the whole process of sample melting, automatic detection to eliminate the subjective error to determine the melting point.

Features :

- TFT touch screen display

- Semi- automatic detection method, with cooling function

- Capacity per batch is 2 pcs

- Designed with a key automatic detection function

- Use of double opening capillary size I.D>1.0 mm,O.D.1.4 mm

- In line with international standards such as CE & ISO

- Adopted with Peltier precise temperature function technology

Specifications :

Temperature control range	6 to 100°C
Detection method	Semi-automatic
Capacity per batch	2 pcs/batch
Temperature resolution	0.1°C
Temperature gradients	(0.1 to 10.0)°C/Min
Temperature accuracy	±0.3°C
Repeatability	0.1°C/Min , ±0.1°C
Camera & Video	Camera & Video
Video playback	Yes
Operator account	8
Result storage	400
SD card capacity	8G
Display	TFT Touch screen
Interface	USB RS232 SD card Ethernet
Opening capillary size	I.D>1.0 mm, O.D.1.4 mm Double opening
Power	110 to 220V 50, 60HZ 120W
Dimension	400 × 280× 330 mm
Weight	5 kg

Applications :

It finds application across finding melting point of oil and fat in food and drug industry, biochemistry, medicines, mining, water management

industry.



Quatro House, Lyon Way, Camberley, Surrey GU16 7ER United Kingdom

Email: info@Labtron.com | Website: www.labtron.com