



ORDER CODE **HV000421**

XL421

TRMS SINGLE-PHASE CURRENT DATA LOGGER



XL421 is a **Data Logger** capable of measuring and recording the true root mean square(**TRMS**) value of AC current up to **2500A** in **single-phase** electric systems for different applications (evaluation of load currents, rated powers of transformers, etc.). The device is enclosed in a practical waterproof plastic case with integrated flex clamp jaws able to surround also a big-sized cable or bar. Thanks to an advanced memory management algorithm it is possible to monitor a system even for a long time. The device starts recording with a **sampling period** which can be selected through software among 1, 6, 30 and 60 seconds and, when memory is almost full, the previously recorded values are “re-sampled” according to the subsequent value of the sampling period, thus freeing part of the memory; the device then goes on recording new values, using the new measuring interval. In this way, it is possible to keep the device recording up to **approximately 1 year**. Each recording is kept stored in the internal memory and can be **downloaded and managed by PC** always through a dedicated software. Data Logger XL421 is also provided with a special adhesive strap which makes it possible to place it in any place in the installation where measuring is needed. The high protection rating (**IP65**) makes this device fully reliable also under extreme operating conditions.



ORDER CODE **HV000422**

XL422

TRMS THREE-PHASE CURRENT DATA LOGGER



XL422 is a **Data Logger** capable of measuring and recording the true root mean square(**TRMS**) value of AC current up to **2500A** in **three-phase** 3-wire electric systems for different applications (evaluation of load currents, rated powers of transformers, etc.). The device is enclosed in a practical waterproof plastic case with integrated flex clamp jaws able to surround also big-sized cables or bars. Thanks to an advanced memory management algorithm it is possible to monitor a system even for a long time. The device starts recording with a **sampling period** which can be selected through software among 1, 6, 30 and 60 seconds and, when memory is almost full, the previously recorded values are “re-sampled” according to the subsequent value of the sampling period, thus freeing part of the memory; the device then goes on recording new values, using the new measuring interval. In this way, it is possible to keep the device recording up to **approximately 90 days**.

Each recording is kept stored in the internal memory and can be **downloaded and displayed on the PC** always through a dedicated software. Data Logger XL422 is also provided with a special adhesive strap which makes it possible to place it in any place in the installation where measuring is needed. The high protection rating (**IP65**) makes this device fully reliable also under extreme operating conditions.



Functions and characteristics

- TRMS single-phase current measurement
 - Measuring range: 1 ÷ 2500A AC
 - Accuracy: ±(1.0%reading+1 digit)
 - Resolution: 1A
 - Operating frequency: 50±6Hz, 60±6Hz
 - Bandwidth: 3200Hz
 - Sampling frequency: 64 spots in 20ms
 - Integration period: 1s, 6s, 30s, 60s, 5min
 - Memory capacity: 1Mbyte
 - Serial interface: RS-232
 - Integration period.....duration in days:
 - 1s.....5
 - 6s.....34
 - 30s.....170
 - 60s.....364(*)
 - 5min1820(*)
 - Front panel indication: LED diodes
 - Power supply: 2x1.5V batteries type AA LR6
 - Battery life: >6months (with loaded batteries)
 - Safety: IEC/EN 61010-1
 - Measurement category: CAT IV 600V (to earth)
 - Insulation: Double insulation
 - Pollution level: 2
 - Mechanical protection index: IP65
 - Max height: 2000m
 - Max diameter of flex clamps: 174mm
 - Size (LxWxH): 120x80x43 mm
 - Weight (batteries included): approx. 0.5kg
- *according to battery duration*



Accessories provided

VELCRO	Adhesive strap 50x70mm
TOPVIEW2004	Windows software for PC + serial cable C2004
BORSA 2000	Soft carrying bag
	Batteries
	User Manual



Optional accessories

C2009	RS232-USB adapter
-------	-------------------



Functions and characteristics

- TRMS three-phase current measurement
 - Measuring range: 1 ÷ 2500A AC
 - Accuracy: ±(1.0%reading+1 digit)
 - Resolution: 1A
 - Operating frequency: 50±6Hz, 60±6Hz
 - Bandwidth: 3200Hz
 - Sampling frequency: 64 spots in 20ms
 - Integration period: 1s, 6s, 30s, 60s, 5min
 - Memory capacity: 1Mbyte
 - Serial interface: RS-232
 - Integration period.....duration in days:
 - 1s.....1.5
 - 6s.....8
 - 30s.....42
 - 60s.....91
 - 5min455(*)
 - Front panel indication: LED diodes
 - Power supply: 2x1.5V batteries type AA LR6
 - Battery life: >6months (with loaded batteries)
 - Safety: IEC/EN 61010-1
 - Measurement category: CAT IV 600V (to earth)
 - Insulation: Double insulation
 - Pollution level: 2
 - Mechanical protection index: IP65
 - Max height: 2000m
 - Max diameter of flex clamps: 174mm
 - Size (LxWxH): 120x80x43 mm
 - Weight (batteries included): approx. 0.5kg
- *according to battery duration*



Accessories provided

VELCRO	Adhesive strap 50x70mm
TOPVIEW2004	Windows software for PC + serial cable C2004
BORSA75	Soft carrying bag
	Batteries
	User Manual



Optional accessories

C2009	RS232-USB adapter
-------	-------------------