

Digital Measuring Tape and Laser Distance Measurer

DIGI PLUS-LINE® Electr. Digital Measuring Tape

- exceptional tape stability • LCD display with clear digits
- weatherproof housing • lies save and non slip in your hand
- rugged and rubber covered housing with stainless metal clip and lanyard
- yellow coated blade, high rubb-off resistant
- self adjusting end-hook, automatic blade return and blade stop
- adjustable readout in display from either side of the housing, mm/inch switchable
- black/red figures, black graduation, no holes punched in the blade
- zero setting at any position, with data hold function, On/Off button
- incl. 1x 3 V battery (type CR2032, art.-no.: 2002093), and operation manual





| ART NO | mm / inch | mm | max. ± mm | mm | mm | mm | KG | ART NO CC |
|--------|-------------|----|--------------|----|--------------|------|-------|--------------|
| 140105 | 5 m / 16 ft | 1 | 1.5 | 19 | 75 x 70 x 32 | 1700 | 0.212 | 1494105 |

BLUE-LINE® Telescopic Measuring Rod with analogous reading display at eye level

NEW






- for distance measurement
- suitable for craftsmen and construction
- made of weatherproof aluminium, elements can be locked individually
- with two vials, for adjustment of horizontal and vertical reading
- window for reading the measuring length



| ART NO | mm | mm | KG |
|----------|------------|----------------|-------|
| 143003.2 | 655 - 3040 | 655 x 120 x 40 | 1.300 |
| 143005.2 | 910 - 5010 | 910 x 120 x 40 | 1.800 |

DIGI PLUS-LINE® Laser Distance Meter • IP41

- modern device with colour display
- the instrument measures distance, area and volume
- distances can be added or subtracted
- indirect measuring for height measuring
- calculation of angles and triangular areas, trapezoidal faces and much more
- Pythagoras-Function 1: calculation of distance using two related measurements
- Pythagoras-Function 2: calculation of distance using two related measurements
- „low-battery-display“, with backlight, memory function for 20 measurements
- measuring in meter, inch or engl. feet, measurement speed 0.5 sec.
- autom. power off: laser beam after ~20 sec., device after ~5 min.
- operation temperature -10° ~ +40°C, storage temperature -20° ~ +60° C
- user-friendly rubber buttons, sound signal by pressing the buttons
- laser class II, FCC test part 15, EN 60825-1:2007 and others
- laser parameter 620 - 660nm, output max. 1mW
- carrying bag with belt loop, hand loop, 2 x 1.5 V battery (type AAA, art. no. 609283) and operation manual



| ART NO | m | m | max. ± mm | nm | mW | mm | KG | ART NO CC |
|--------|----------|-------|--------------|-----|--------|---------------|-------|--------------|
| 140130 | 0.5 - 80 | 0.001 | 2 | 650 | max. 1 | 120 x 50 x 25 | 0.130 | 1494100 |