Exemplar® Plus

High Performance Smart Spectrometer



SIGNAL TO NOISE RATIO:				
On-board averaging 1	~540			
On-board averaging 10	~1900			
On-board averaging 100	~4800			

The Exemplar® Plus is a high performance smart spectrometer utilizing a low stray light unfolded Czerny-Turner spectrograph. It features a highly sensitive TE cooled back-thinned (BT) CCD detector which is linearly summed for high dynamic range. Its long focal length, coupled with a high quantum efficiency detector, provides superior data quality over the entire 190-1100nm spectral range. The Exemplar Plus features a high signal to noise ratio, making it ideal for low light level applications, and also features a built-in shutter allowing for dark scan measurements, even while illuminated. As a member of the Exemplar product line, it features on board data processing and USB 3.0 communication. The Exemplar product line is also optimized for multichannel operation featuring ultra-low trigger delay and gate jitter.

The Exemplar Plus is available in the following standard configuration: wavelength range of 190-1100nm, 25µm slit, an LVF filter, a ruled grating (300mm/280nm), and a spectral resolution of 1.8nm. Custom configurations are also available.

SMART:

pectrometa

On-board processing including averaging, smoothing, and dark compensation

SPEED:

Acquires and transfers more than 140 spectra per second at an integration time of 6.3ms

SYNCHRONOUS:

Supports up to 32 devices with ultra-low trigger delay (95ns) & gate jitter (+/- 20ns)



Applications:

- Low light level UV to NIR spectroscopy
- Raman and fluorescence spectroscopy
- **On-line process monitoring**
- LCD display measurement
- **Biomedical spectroscopy**
- Gas and water analysis
- **LED** characterization

Back	2.6297 mg 2.6297 mg 2.4061 mg	25651 ms 25651 ms 2000 10,3991 ms	16.3336 no 2007 4.1162 ms	☑ ZABN 12.2247 ms ☑ ZDMS 3.2348 ms	PLM 10.6829 ms 200H 3.5359 ms	₹ 2802 3.8156 ms ₹ 2008 4.6215 ms	2 5428 ms	2 2358 ms 2 2358 ms 2 2358 ms 4 8341 ms	
Acquire	15000 + 10000 + 6000 - 0 -	2849°	1500	15000 + 10000 + 5000 - 0 - 500	1000 1500 (pvelength	20000 15000 10000 5000 0	-	1500 2000 night	5000 + 5000 5000 Witnestingth
Stop	8000 ±	PLM		8000 ‡ 8000 ‡	BUZ	6000 -	ZBVA		28VE 9000 + 9000 +
Save	2000	io todo sti Wavelength	00		000 1500 20 avelength	2000 -	500 1000 Wavelet	1500 2000 ngth	9 500 0000 16 Warehength
Reset	10000 +	28VD	100	4000 + 4000 + 500	soco teoo avalength	6000 - 4000 - 2000 -		1500 2000 ngth	2045 6000 + 2000 2000 - 2000 0 500 1000 150 Warelength
	8000 T 8000 T 4000 T	ZDUH		10000 +	DUI	10000	ZDMR		204A 10000 + 5000 +
BWTEK:	0	500 1000 1	1500	500	1000 1500	0	500 10	000 1500	500 1000 150

Specifications:


Power Input	5V DC @ 6A (maximum at startup) 5V DC @ 2.5A (typical at normal operation)
Detector Type	Back-thinned CCD Array
Wavelength Range	190nm - 1100nm
Detector Pixel Format	2048 effective detector elements
Effective Pixel Size	14μm x ~ 0.9mm
Spectrograph f/#	3.6
Spectrograph Optical Layout	Standard Czerny-Turner
Dynamic Range	50,000 (Typical)
Digitizer Resolution	16-bit or 65,535:1
Data Transfer Speed	>140 Spectra per second at integration time of 6.3ms in burst mode
Trigger Delay	95ns +/- 20ns (call for timing diagram)
Readout Speed	> 400kHz
Integration Time	6.3ms, adjustable in 1μs increments
Aux Port	External trigger, 4 digital outputs (2 with shutter control), 2 digital inputs, analog input, analog output and system reset
Operating Temperature	5°C - 35°C
Operational Relative Humidity	85% noncondensing
CCD Cooling	Default: 0°C at ambient of 25°C.
Weight	3.6 lbs
Dimensions	7.40in x 5.05in x 2.80in (188mm x 128mm x 71mm)
Computer Interface	USB 3.0 / 2.0
Operating Systems	Windows: 7, 8 (32-bit & 64-bit)

Additional Features:

- High UV, Vis, and NIR response
- 2048 detector elements
- Over 60% OE at 200nm
- Configurable cooling temperature (0° default)
- Over 90% peak QE
- Built-in shutter

Software:

BWSpec® is a spectral data acquisition software with a wide range of tools that are designed to perform complex measurements and calculations at the click of a button. It allows the user to choose between multiple data formats and offers optimization of scanning parameters, such as integration time. In addition to powerful data acquisition and data processing, other features include automatic dark removal, spectrum smoothing, and manual/auto baseline correction.





Slit Option	Dimensions	Approx. Resolution 350 -1050nm		
10μm	10μm wide x 1mm high	~1.2nm		
25µm	25μm wide x 1mm high	~1.5nm		
50μm	50μm wide x 1mm high	~2.4nm		
100µm	100μm wide x 1mm high	~4.8nm		
Custom Slit Widths Available				

Diffraction Grating

Best Efficiency	Spectral Coverage (nm)	Grating		
Vis / NIR	350-1050	400/550		
NIR	750-1050	830/900		
UV- NIR	190-1100	300/280		
UV - NIR	200-850	400/250		
UV	190-380	1500/250		
Custom Configurations Available				

Accessories:

- Fiber sampling probes
- Fiber sample holders
- Fiber patch cords
- Light sources

Spectrograph

